

SPECIFICATION Q POCCO MM



	YX	ZX
Configuration name	3025*1500*1515	3025*1500*1515
Length* width* height(mm)	1950	1950
Wheel base(mm)	> 120	> 120
Minimum ground clearance(mm)	< 8	< 8
Minimum turning diameter(m)	1300/1300	1300/1300
Front/rear wheel track(mm)	116	170
NEDC (km)	750	750
Curb weight (kg)	PMSM	PMSM
Motor type	20	20
Maximum motor power (kW)	100	100
Maximum motor torque(Nm)	100	100
Maximum speed(km/h)	Lithium-ion battery	Lithium-ion battery
Power battery type	220	220
Charging voltage(V)	9.2KWH	14KWH
Power battery capacity	6-8 hours	6-8 hours
Charging time(h)	A/C	A/C
Air conditioner	fabric	fabric
Seat fabric	Main/First Officer seat adjustment	four directional
Main/First Officer seat adjustment		

SPECIFICATION Q POCCO DD



	DD L	DD K
Configuration name	3310*1500*1588	3310*1500*1588
Length* width* height(mm)	2275	2275
Wheel base(mm)	> 120	> 120
Minimum ground clearance(mm)	9.9	9.9
Minimum turning diameter(m)	1300/1300	1300/1300
Front/rear wheel track(mm)	> 128	> 178
NEDC (km)	750	805
Curb weight (kg)	PMSM	PMSM
Motor type	29	29
Maximum motor power (kW)	110	110
Maximum motor torque(Nm)	> 100	> 100
Maximum speed(km/h)	Lithium-ion battery	Lithium-ion battery
Power battery type	220	220
Charging voltage(V)	10.3KWH	14.5KWH
Power battery capacity	6-8 hours	6-8 hours
Charging time(h)	155/65 R13	155/65 R13
Tire type	fabric	fabric
Seat fabric	Main/First Officer seat adjustment	four directional
Main/First Officer seat adjustment		



POCCO



POCCO
POCCO(THAILAND)CO.,LTD.

HOTLINE
081-819-8894

FASHION
SMALL NEW TREND FINE

นวัตกรรมรถยนต์ EV มัลติฟังก์ชันครบครัน

บริษัทฯ ขอสงวนสิทธิ์ในการเปลี่ยนแปลงราคา รายละเอียด และอุปกรณ์ต่างๆ ข้างต้น โดยไม่ต้องแจ้งให้ทราบล่วงหน้า