STANDARD EQUIPMENTS

MITSUOKA

Details \ Model	Galue-Ⅳ		
	G-XV250 (Sunroof)	G-XV250	G-XL200
Exterior equipment			
Sunroof One Touch	O	-	-
Front head lamps: Multi Reflector (with manual levelizer)	-	-	O
Auto Leveling Headlight System	O	O	-
Front wipers: Variable intermittent and Speed sensing	O	O	O
Door mirrors: Electric foldable and adjustment	O	O	O
Door mirror with Side Turning lamps	O	O	O
Door mirrors: Reverse synchronization	O	O	-
Tire	215/55R17		205/65R16
Alloy Wheel	O	O	O
Interior			
Interior Color	Beige		
Steering Wheel: Tilt Adjustment	O	O	O
Cruise Control	O	O	O
Push Start Button	O	O	O
Intelligent Key with Immobilizer and Panic Alarm	O	O	O
Central Door Lock	O	O	O
Speed Sensing Auto Door Lock	O	O	O
MID (Multi-Information Display)	O	O	O
Rear mirror: Auto-dimming mirror with Compass	O	O	-
Power Window with Anti-jam Protection at driver window	O	O	O
Genuine and synthetic leather seat	O	O	O
Seat: Driver Electric adjustment 8 directions with lumbar support	O	O	O
Seat: Front Assist Electric adjustment 4 directions	O	O	O
Memory Seat with 2 memories for driver	O	O	-
Rear Armrest with cub holder	O	O	O
Rear Seat: trunk access	O	O	O
Auto Air Conditioning with dual climate control	O	O	O
Rear A/C Duct	O	O	O
Power Rear Sunshade	O	O	O
Stainless Side Step Garnish	O	O	O
Audio			
6 CDs changer , MP3 Function and 6 Speakers	O	O	O
Aux-in	O	O	O
Audio & Cruise Control control switch on steering wheel	O	O	O
Antenna: in glass	O	O	O
Safety			
SRS Airbags	O	O	O
Side Airbags	O	O	-
Curtain Airbags	O	-	-
VDC with Traction Control	O	O	-
ABS + EBD + BA	O	O	O
Rear Parking Sensor (4 points)	O	O	O
Active Head Restraints	O	O	O
Child seat retainer	O	O	O
Rear Seat Belt 3 points x 3	O	O	O
Pre-tensioner and Load Limiter Seatbelts	O	O	O
Water repellent window mirrors	O	O	O
High-mounted stop lamp	LED		

O Available

- Not available

MITSUOKA MOTOR SALES (THAILAND) CO., LTD.


SPECIFICATIONS

MITSUOKA

Detail \ Model		MITSUOKA Galue-IV		
		G-XV250 (Sunroof)	G-XV250	G-XL200
Engine				
Model		VQ25DE		MR20DE
Type		V6 DOHC 24 Valve CVTC with NICS		Inline4 DOHC 16 Valve CVTC
Engine Displacement	(cc)	2,496		1,997
Bore x Stroke	(mm)	85.0 x 73.3		84.0 x 90.1
Compression Ratio		9.8:1		10.0:1
Power	PS (kW)/rpm	182 (134) / 6,000		136 (100) / 5,600
Torque	Nm (kg-m)/rpm	228 (23.2) / 4,400		190 (19.4) / 4,400
Transmission		XTRONIC CVT		
Forward Gear Ratios		2.349 - 0.394		
Reverse Gear Ratios		1.750		
Final Gear Ratios		6.120		6.466
Steering system				
Type		Twin Orifice Vehicle Speed Sensing Power Steering (TOPS)		
Turning radius	(m)	5.7		5.3
Brake system				
Front		Ventilated Disc		
Rear		Solid Disc		
Suspension				
Front		Independent struts with stabilizer		
Rear		Multi-link independent		
Dimension				
Length	(mm)	4,980		
Width	(mm)	1,795		
Height	(mm)	1,475		
Wheelbase	(mm)	2,775		
Front/Rear treat	(mm)	1,550/ 1,555		1,560/ 1,565
Ground Clearance	(mm)	135		
Trunk	L (VDA)	506		
Weight	(kg)	1,540		1,450
Fuel tank capacity	(Liters)	70		

BODY COLORS


◆ White Pearl




◆ Black Star



◆ Deep Amethyst Grey



◆ Brilliant Silver



◆ Greyish Bronze



